

UNCLASSIFIED

AD NUMBER	
AD361292	
CLASSIFICATION CHANGES	
TO:	unclassified
FROM:	secret
LIMITATION CHANGES	
TO:	Approved for public release, distribution unlimited
FROM:	Distribution authorized to U.S. Gov't. agencies only; Foreign Government Information; 03 MAY 1965. Other requests shall be referred to British Embassy, 3100 Massachusetts Avenue, NW, Washington, DC 20008.
AUTHORITY	
DSTL, AVIA 16/200, 10 Feb 2009; DSTL, AVIA 16/200, 10 Feb 2009	

THIS PAGE IS UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

NOTICE:

THIS DOCUMENT CONTAINS INFORMATION
AFFECTING THE NATIONAL DEFENSE OF
THE UNITED STATES WITHIN THE MEAN-
ING OF THE ESPIONAGE LAWS, TITLE 18,
U.S.C., SECTIONS 793 and 794. THE
TRANSMISSION OR THE REVELATION OF
ITS CONTENTS IN ANY MANNER TO AN
UNAUTHORIZED PERSON IS PROHIBITED
BY LAW.

CATALOGED BY: DDC 361292 L
AS AD NO. 361292 L

COPY No. 78

SECRET

MINISTRY OF AVIATION

AIRCRAFT TORPEDO DEVELOPMENT UNIT

HELSTON
CORNWALL

PROGRESS REPORT

U

AVAILABLE COPY WILL NOT PERMIT
FULLY LEGIBLE REPRODUCTION.
REPRODUCTION WILL BE MADE IF
REQUESTED BY USERS OF DDC.

A P R I L 1 9 6 5
.....
1. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
2. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
3. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
4. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
5. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
6. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
7. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
8. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
9. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
10. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
11. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
12. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
13. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
14. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
15. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
16. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
17. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
18. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
19. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
20. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
21. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
22. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
23. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
24. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
25. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
26. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
27. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
28. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
29. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
30. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
31. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
32. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
33. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
34. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
35. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
36. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
37. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
38. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
39. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
40. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
41. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
42. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
43. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
44. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
45. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
46. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
47. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
48. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
49. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
50. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
51. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
52. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
53. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
54. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
55. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
56. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
57. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
58. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
59. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
60. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
61. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
62. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
63. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
64. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
65. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
66. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
67. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
68. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
69. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
70. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
71. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
72. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
73. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
74. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
75. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
76. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
77. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
78. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
79. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
80. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
81. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
82. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
83. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
84. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
85. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
86. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
87. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
88. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
89. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
90. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
91. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
92. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
93. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
94. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
95. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
96. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
97. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
98. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
99. THE FOLLOWING INFORMATION IS FOR THE USE OF THE
100. THE FOLLOWING INFORMATION IS FOR THE USE OF THE

THIS DOCUMENT IS THE PROPERTY OF H.M. GOVERNMENT
AND ATTENTION IS CALLED TO THE PENALTIES ATTACHING
TO ANY IMPROVEMENT OF THE OFFICIAL SECRETS ACTS

It is intended for the use of the recipient only, and for communication to such officers under him as may require to be acquainted with its contents in the course of their duties. The officers exercising this power of communication are responsible that such information is imparted with due caution and reserve. Any person other than the authorized holder, upon obtaining possession of this document, by finding or otherwise, should forward it together with his name and address in a closed envelope to:-
THE SECRETARY, MINISTRY OF AVIATION, ADELPHI, LONDON, W.C.2.

Letter postage need not be prepaid, other postage will be refunded. All persons are hereby warned that the unauthorized retention or destruction of this document is an offence against the Official Secrets Act.

DDC
JUN 16 1965
RECEIVED
JISIA D

52155

SECRET

EXCLUDED FROM AUTOMATIC
REGRADING: DOD DIR 5200.10
DOES NOT APPLY

S E C R E T

Ministry of Aviation,
Aircraft Torpedo Development Unit,
Helston,
Cornwall.

3rd May 1965

Progress Report No 1/65

TDU/61/06

Aircraft Torpedo Development Unit

Half-Yearly Progress Report

April 1965

This report concerns the work completed during the period 1st November 1964. to 30th April 1965.

The number of trials completed increased over comparable periods in recent years; Wessex clearance trials in respect of DME buoys and Depth Charges have been made on behalf of A. & C.E.E.

This Unit participated in the Wessex H S Mk 5 Winterisation trials in Canada and recommendations have been made in respect of Mk 44 torpedo and fuze design, and minor modifications to flight-in-air material have been initiated.

Arrangements have been provisionally made with R.A.E. permitting the use of a Canberra BI.6 aircraft as the test vehicle for high speed release trials of Mk 44 torpedoes.

Mr. W. W. W.

Superintendent

S E C R E T

S E C R E T

LIST OF CONTENTS

<u>PART I</u>	-	<u>AIRCRAFT INSTALLATION WORK IN PROGRESS</u>
1.1	-	Wessex HAS Mk 1
1.2	-	Wasp HAS Mk 1
1.3	-	Gannet AEW Mk 3
1.4	-	Shackleton Mk 2 and 3 (Phase 3)
<u>PART II</u>	-	<u>TORPEDO AND MINE PROJECTS</u>
2.1	-	18" Mk 30 torpedo
2.2	-	Mk MC 43-3 torpedo
2.3	-	UK Mk 44-0 torpedo
2.4	-	Breakaway suspension band Type 'C'
2.5	-	UK Mk 44 torpedo airborne presetter
2.6	-	Parachute Attachment type AT/L
2.7	-	Delivery system for high speed aircraft launching of UK Mk 44/Mk 46 A/S torpedoes
2.8	-	Delivery system for launching A/S torpedo from 150K helicopter
2.9	-	Twin break way suspension band for UK Mk 44 torpedo
2.10	-	UK torpedo project delivery system
2.11	-	NATO Meeting Mk 44 torpedo interchangeability
<u>PART III</u>	-	<u>MISCELLANEOUS PROJECTS</u>
3.1	-	Helicopter recovery
3.2	-	A/S bomb trials
3.3	-	Special tool for Type C band
3.4	-	Torpedo recovery
<u>PART IV</u>	-	<u>INSTRUMENTATION AND ANALYSIS IN SUPPORT OF TRIALS</u>
4.1	-	Recording peak shock loads
4.2	-	High speed recording
4.3	-	Accelerometer calibration rig (vibrating beam)
4.4	-	Drop test machine
4.5	-	Centrifugal calibrator
4.6	-	Torpedo recorders
4.7	-	A.T.D.U. tape recording equipment
4.8	-	Instrumentation for outer ranges
4.9	-	Readout facility for magnetic tape results
<u>PART V</u>	-	<u>WORK CARRIED OUT FOR OTHER DEPARTMENTS</u>
5.1	-	Pyrotechnics
5.2	-	Wasp transponder aerial
5.3	-	R.N. gun blast trials - Wasp helicopter
5.4	-	Depth charges, carriage and release - Wessex HAS Mk 1
5.5	-	DME buoys, carriage and release - Wessex HAS Mk 1 and Mk 3
<u>PART VI</u>	-	<u>ENVIRONMENTAL TESTING OF TORPEDOES AND FLIGHT IN AIR MATERIAL</u>
6.1	-	Vibration measurement using MIDAS tape recording instrumentation
6.2	-	Shock measurement using A.T.D.U. tape recording equipment
6.3	-	Shock measurement using mechanical and other electronic instruments
6.4	-	Low temperature test on torpedoes and flight-in-air material

S E C R E T

S E C R E T

PART I - AIRCRAFT INSTALLATION OF THE PROGRESS

1.1 1ST SUX HLS Mk 1

- (a) 2 x 18" Mk 30 - Full release clearance now given. Tests completed.
- (b) 2 x UK Mk 44-0 - Aircraft to Mod 5050 (i.e. with Mk 44 torpedo presetter fitted) now being cleared for torpedo release.
- (c) 2 x Mk 43-3 (primary battery) - Clearance recommended to A. & S. E. and H(d), with copy of letter to U.G. (U). (Naval).
- (d) 2 x 250 lbs Mark 11 depth charges - Clearance trials completed. Includes recommendation for re-positioning No 1 Mark 1 fuze unit on rear boom located to accept the depth charge arming wire.
- (e) 8 x DUT buoys - Carriage and release trials have been completed on behalf of A. & S. E. and the aircraft clearances recommended for Vessex HLS Mk 1 and Mk 3.

1.2 VLSP HLS Mk 1

- (a) 2 x Mk 43-3 (primary battery) - Torpedo release trials in progress
- (b) 2 x UK Mk 44-0 - Release trials completed. Clearance recommended to A. & S. E. F.

1.3 GRINLET Mk 3

2 x UK Mk 44-0 - Cleared for release of torpedoes from the pylon installation at speeds up to 180 knots in level flight. Trials to investigate release of torpedoes at higher speeds and in dives, not exceeding 300 or 240 knots air speed, completed. The full clearance is being recommended to A. & S. E. F.

1.4 SP GRINLET Mk 2 and Mk 3 (Phase 3)

- (a) 18" Mk 30 and (b) UK Mk 44-0

Mk 3 Phase 3 aircraft - Interim torpedo release clearance issued by A. & S. E. F. in December 1964 following joint A. & S. E. F./A. T. D. U. torpedo release clearance trials.

Full torpedo release clearance trials completed in February 1965.

Mk 2 Phase 3 aircraft - Aircraft expected July/August 1965 for torpedo dropping trials.

NOTE - Full details of progress made in respect of these installations are given in Part II or Part III under the appropriate project headings.

S E C R E T

PART II - TORPEDO AND MINA PROJECTS

2.1 18" Mk 30 torpedo

(a) Release from helicopter aircraft

(i) Vessex HAS Mk 1

Action Mk 30 now cleared for release over speed range Hover to Maximum, at heights of 30 ft and above. Item completed.

(b) Release from fixed wing aircraft

Both action (primary battery) and exercise (secondary battery) torpedoes have been released satisfactorily from Shackleton Mk 3 Phase 3 aircraft during recent trials. Item completed.

2.2 Mk RC 43-3 torpedo

D.C.M.(U) N.O.D. (Naval) requires the Royal Navy to have a facility for Mk 43-3 torpedoes, fitted with the Canadian built Mk RC 78 Mod 0 primary battery, to be released from Vessex and Asp aircraft.

Trials have shown that with minor modification to the torpedo battery arming lanyard and to the Vessex torpedo carrier boom this requirement can be met and clearance of the Vessex for release of Mk 43 Mod 3 (primary battery) torpedoes has been recommended to A. & A.F.E. and H(d). Further action is required by H(d) to promulgate the clearance.

Trials employing the Asp aircraft are progressing satisfactorily.

2.3 UK Mk 44-0 torpedo

(a) Release from fixed wing aircraft

(i) Gambet / EW Mk 3

Further trials have taken place to clear the aircraft for release of UK Mk 44-0 torpedoes, fitted with parachute attachment type T/I and breakaway band type C, from the wing pylon installation at speeds above 180 knots and in 30° dives. The trial results are being discussed with A. & A.F.E. and a full clearance is being recommended.

(ii) Shackleton Mk 3 Phase 3

A. & A.F.E. aircraft completed torpedo release trials at F.T.D.U. in February, UK Mk 44 torpedoes, fitted with AT/I parachute attachment and breakaway band type C, were satisfactorily pre-set in the air, using the airborne pre-setter, and released from all Mk 44 stations on the aircraft. Torpedo running behaviour following air launch was satisfactory.

(b) Release from helicopter aircraft

(i) Vessex HAS Mk 1

Vessex aircraft of 706 Squadron, Culdroe has been fitted to Mod. 5050 standard to enable torpedo release clearance trials to take place. This modification introduces the torpedo airborne presetter and modifies existing Mk 30/43 torpedo carriers to accept the UK Mk 44-0 torpedo.

S E C R E T

A number of runner UK Mk 44 torpedoes, fitted with parachute attachment type W/K and breckaway band type C have been released from the modified aircraft with satisfactory results. A clearance note is in preparation.

(ii) Resp HAS Mk 1

Aircraft fitted with the modified engine, and cleared to lift 5,500 lbs, has been used in trials to clear the aircraft for release and jettison of 2 x UK Mk 44-0 torpedoes. Report is in preparation

2.4 Breckaway suspension band type "C"

Full approval has been given and manufacture commenced.

Trials at the Winter Experimental Establishment in Canada showed the breckaway band to operate satisfactorily in torpedo dropping trials, but that the lanyard pull out force could reach a figure such that the associated weak link was in a marginal condition.

A simple modification to the timer rack has been successfully tried to overcome this difficulty.

It is proposed to submit this modification for incorporation in subsequent production batches of bands.

2.5 UK Mk 44 airborne presetter

Operation in Shackleton and Wessex aircraft has been satisfactory.

2.6 Parachute attachment type AT/L

Production of this attachment, employed to air launch the UK Mk 44 torpedo from fixed wing aircraft, is now in progress.

Some work has taken place on a prototype inertia release mechanism which may simplify production of the attachment. Some 5 drops of dummy torpedoes fitted with the 'inertia' release have now been made. With a setting less than 8'g' the release operated satisfactorily on 3 occasions. With greater than 10'g' setting the release failed to operate at water entry of the torpedo.

Several modifications have been carried out and proving trials are in hand.

A rubber cover has been designed and produced for this attachment and initial trials are proving very satisfactory.

2.7 Delivery system for high-speed aircraft launching of UK Mk 44

Mk 46 anti-submarine torpedoes

In view of the expected in service life of the UK Mk 44 torpedo and variants, P.T.D.U. are engaged in developing a two-stage parachute system suitable for their delivery from aircraft capable of 400 knots airspeed, i.e. Shackleton replacement. The basic design has been finalised and detail drawings for the two-stage prototypes, to be manufactured at P.T.D.U., are in preparation.

A detailed design study is being carried out and a survey has been made of existing time mechanisms. As a result it has been decided to proceed with an P.T.D.U. clockwork type mechanism and work is proceeding along these lines.

S E C R E T

A dummy housing incorporating the system devised for the first stage parachute release has been designed and two are being made in the workshops to enable trials to be carried out investigating the bulk problems of stowing the two parachutes supplied by Messrs G.O. & Co. and the deployment of the first stage release mechanism. Blower tunnel trials are being arranged.

The design will be such that if required the attachment can by simple modification, also be used to air launch the Mk 46 torpedo under similar conditions.

Approval is being sought for the flight evaluation of the system to be made using a BI 6 Canberrra from R.A.F. Farnborough.

Preliminary discussions with R.A.E. and English Electric, Warton have been satisfactory and a procedure and provisional programme agreed.

A T.I. of 2 x Mk 44 torpedoes will be attempted at R.A.E. on 5th May, 1965.

It is proposed that two dummy torpedoes will be instrumented; the first, for preliminary trials will embody an hypotograph and a C.I. Type 3 scratch recorder, the second will embody accelerometer, rate gyros and a galvanometer recorder.

2.8 Delivery system for launching anti-submarine torpedoes from 150 knot helicopter

A preliminary design study has been done on this project, but work is not held up by lack of Drawing Office effort.

2.9 Twin breakaway suspension bands for UK Mk 44 torpedo

T.D.U. have been tasked by D.A. Arm with the design and development of UK twin point suspension bands for the UK Mk 44-0 torpedo, following the Joint Staff policy decision that all future UK aircraft will employ twin point store carriers.

It should be noted that N.O.D. (Naval) decision to fit twin point suspension on Wessex 5 and later Asp aircraft has been reversed.

Design work is in progress and it is intended that the bands will meet the full strength requirements of MIL. SPEC. 8591C. To leave no lanyards on the aircraft a simple time delay will be incorporated in the design.

Specimen UE twin point attachment bands have been obtained and are being evaluated.

2.10 UK torpedo project delivery system

Further discussions have taken place with the Torpedo Research Section of A.U.W. on possible delivery systems for the UK torpedo project.

With the design at present envisaged it may prove possible for the parachute system to attach to the tail cone of the torpedo, rather than to the propeller shaft. If higher parachute opening shock loads on the torpedo are then permitted a single parachute could be employed, possibly in conjunction with a protective frangible nose cap fitted to the torpedo.

A.U.W. have called a meeting of all interested authorities to discuss the torpedo and possible delivery systems and other allied problems on 27th May, 1965 at A.R.I. Teddington.

S E C R E T

Information regarding frangible nose cones is sparse and it is suggested that a program to investigate their use would be worthwhile.

2.11 NATO Meeting II: Mk 44-O torpedo interchangeability

The UK proposal that torpedo flight-in-air material should be treated as a separate issue from that of torpedo and component interchangeability was not adopted at the last meeting.

It was however, agreed that the UK T/L parachute attachment and the US Mk 24 attachment would be interchangeable if both were supplied with their appropriate torpedo tail nut in the parachute container. A recommendation to this effect has been submitted to C.O.D. (Naval) and C.O.D. (Air).

PART III - MISCELLANEOUS PROJECTS4.1 Helicopter Recovery

Nothing further to report, still awaiting minor modifications for incorporating in Master Drawings from C.U. Yard, Fleetlands.

4.2 AS bomb trials

There have been no further trials.

4.3 Special tools for type 'C' bands

A production batch of 20 sets of tools have been made and supplied for R.F. use.

5.4 Torpedo recovery

When using the line and grab system for recovering negatively buoyant stores, some difficulty has been experienced in handling the store inboard after it has been lifted. The problem is more acute with stores containing delicate instruments. Discussions with 1102 C.U. are about to be held with a view to producing some simple device which will enable the stores to be brought inboard with less difficulty.

S E C R E T

PART IV - INSTRUMENTATION AND ANALYSIS IN SUPPORT OF TRIALS

4.1 Recording peak shock loads

(a) The electronic shock register was lost during trials on 18th November 1964. A replacement was made to the same design and this was ready in early February.

Initial design work on the shock monitors has started.

(b) The original "Impactograph" recorder was lost with the shock register.

4.2 High-speed recording

This equipment is now completed.

4.3 Acceleration amplification and vibration test

The instrument is now completed, but photographic trials have yet to be made. These may show that a special mounting is necessary.

4.4 Drop test machine

The workshops have completed their work on this machine. Initial test recordings revealed some difficulty due to noise from the transducer cables. The Instrumentation Section have already made use of the facility to check the operation of the peak "g" box, and its readings were found to agree with the direct measurement. The Development Section are now using this machine to study the action of the inertia release at water entry, after which it will be used in the development of the A.T.D.U. tape recorder mount. When the more pressing commitments have been discharged it is intended to investigate the shock profiles produced by different programmers.

4.5 Centrifugal calibrator

The design for this calibration facility is now completed and the workshops have been directed to give this top priority so that it may be available for setting up the transducers in the shock measuring torpedo XR4.

A set of high quality slip rings and brushes has been obtained, but it has not yet been possible to test them. A simple device for obtaining accurate speed measurements is being designed.

The console to house this unit is being produced using "Midney Dorlec" constructional system.

4.6 Torpedo recorders

There is no longer a requirement for further Mk 36 torpedo recorders and this matter is no longer being pursued.

The main airborne recorders in future will be:-

(a) For flight-in-air and initial dive:

Motorised "Impactograph" and Woodhill galvanometer recorder, to be followed by a Mk 78 head.

(b) For water entry shock:

Tape recording system, backed up by shock monitors for statistical work.

S E C R E T

4.7 M.T.D.U. tape recording equipment

Installation in Mk 44 ex-runner torpedo of Tape Deck, Electronic Panels and shock measuring transducers are well advanced. Sub-assembly drawings and general arrangement are now being produced.

It is hoped to commence the trials programme in August/September 1965.

4.8 Instrumentation for outer ranges

The Type 303 marine radar has been supplied, the installation is held pending delivery of the photographic attachments.

4.9 Readout facility for magnetic tape results

The provision of a simple read out facility for the magnetic tape records obtained from the instrumented stores XR4 is being investigated with D.A. Arm.

S E C R E T

PART V - WORK CARRIED OUT FOR OTHER DEPARTMENTS

5.1 Pyrotechnics

R.A.R.D.E. development testing of the sea-cell operated Smoke and Flame float continued with a release trial of 17 stores in November, 1964 from a R.N. Gannet Mark 5 fitted with light-series carriers within the bomb bay.

A further proofing trial of $3\frac{1}{2}$ lb Smoke and Flame floats was carried out on behalf of D.I. ARM. Woolwich during the same months when 48 stores were dropped from the A. & A.E.E. Mark 3 Phase 3 Shackleton aircraft following a torpedo dropping clearance sortie. The Director, Group Captain C.H. Press, R.A.E. and members of his staff attended the trial as observers.

Arrangements were also made to drop Smoke and Flame floats and anti-submarine target indicators from a Shackleton aircraft from A.S.W.D.U. Ballykelly and, later, from the A. & A.E.E. Shackleton, but last-minute unserviceability of both these aircraft necessitated the use subsequently of a Wessex aircraft with which the trials were satisfactorily conducted.

Limited approval trials of the R.A.R.D.E. Smoke and Flame float are currently being arranged, using a Wessex aircraft, the Admiralty being unable to supply a Gannet aircraft as originally requested.

5.2 Wasp transponder aerial

Nothing further to report.

5.3 R.N. gun blast trials - Wasp helicopter

A.T.D.U. sent a three man team to participate in the Gun Blast trials which were held at H.M.S. Excellent, Portsmouth in January. One dummy Mk 44 torpedo, and one ex-runner Mk 44 instrumented for measuring in-flight vibrations were provided, together with the appropriate flight-in-air material. A. & A.E.E. co-operated in this trial by supplying the Midas recording equipment, and providing personnel to help set up and re-play the tape recordings on their playback facility.

With blast wave pressures at the helicopter of 1 lb/in^2 there was no discernible damage to the aircraft or the flight-in-air material. When the pressure was increased to $1\frac{1}{2} \text{ lb/in}^2$ parts of the canopy showed signs of damage, and the trial was terminated. Some of the results of the shock recording have been analysed, but publication of the results is awaiting re-calibration of the equipment on a shock pulse basis by A. & A.E.E.

5.4 Depth charges, aircraft 250 lbs. Mark 11
Wessex HAS Mark 1 - Carriage and release clearance

Trials to clear the Wessex HAS aircraft for the carriage, handling and release of 2 x 250 lb Mark 11 depth charges have been carried out on behalf of A. & A.E.E. Boscombe Down. The trials were carried out with inert stores only and confirmatory trials with live D.C.s are recommended.

Repositioning of the No 1 Mark 1 rear fuze unit forward of the suggested position is advised, with the use of two Johnstock clips to secure the arming wire instead of the conventional three, so as to lessen the tail-up and oscillatory tendencies of the store on release.

A report has been issued.

5.5 DME buoys
Wessex HAS Mk 1 and Mk 3 - Carriage and release clearance

In a trial conducted on behalf of A. & A.E.C. eight drops were made from a Wessex Mk 1 with wooden dummies from heights of 30 to 200 ft and from the hover to maximum speed. Flight vibration tests were also carried out with operational buoys to see if aircraft vibration could cause separation of the float.

The drops were unstable and bad water entries resulted. The floats remained in position during the various manoeuvres but, there were occasions when it was evident that aircraft vibration was beginning to affect the magnetic hold on the float.

Clearance for the carriage and release of the buoys from the Wessex Mk 1 has been given subject to certain precautions being observed during loading. Further it was recommended both that some form of stabilisation be introduced to control the descent of the stores, and also that a positive method should be devised to lock the float in position during flight.

Although a Mk 3 version of the aircraft was not available, clearance has been likewise recommended since this helicopter is structurally similar to the Mk 1.

The design concept of the float release system is regarded as inferior and it is felt redesign work is necessary

S E C R E T

PART VI - ENVIRONMENTAL TESTING OF TORPEDOES
AND FLIGHT-IN-IR MATERIAL

6.1 Vibration measurements using Mides tape recording instrumentation

- (a) Shackleton MR Mk 2 Phase 2 - clearance for the carriage of Mk 44 torpedoes

The letter report showing overall vibration envelopes has been delayed due to pressure of other work; the results are finalized and the report will be issued shortly.

- (b) Shackleton MR Mk 3 Phase 3 - clearance for the carriage of Mk 30 and Mk 44 torpedoes

Measurements taken from two different types of vibration transducer were not in agreement and further trials were necessary to resolve this problem. As soon as the A. & A.T.E. report is issued giving acceleration versus frequency data this will be analysed at A.T.D.U. on an overall vibration envelope basis and a report will be issued.

- (c) Shackleton MR Mk 2 Phase 3 - clearance for the carriage of Mk 30 and Mk 44 torpedoes

Work is in hand to overhaul the two instrumented torpedoes in readiness for the carriage trials to be held at A. & A.T.E. in June/July.

- (d) Wessex HAS Mk 1 - investigation into vibrations in Mk 30 and Mk 44 torpedoes

This task is now completed: the results were issued in A.T.D.U. Tech. Note No 1/65 in February 1965, copies of which were circulated to all interested departments.

- (e) Gannet AEW 3 - investigations into vibrations in Mk 44 torpedoes

Modifications made to the mounting cradle for the Mides recorder to suit the Gannet AEW 3. Recordings were made of the vibrations in a Mk 44 torpedo when carried on the starboard pylon under various flight conditions. The flight trials were completed in January, and the tape recordings are now being analysed by R.A.E. Weapons Department.

- (f) Vasp H'S Mk 1 - investigations into vibrations in Mk 44 torpedoes

After some initial difficulties with the recorder and the aircraft's power supply had been overcome the flight trials were completed in February 1965. The tape recordings of the vibrations present in the Mk 44 torpedo, when mounted on port and starboard carriers, are being analysed by the Weapons Department of R.A.E.

6.2 Shock measurements using A.T.D.U. tape recording equipment in Mk 44 ex-runner torpedo XRL

- (a) Line recovery system

The initial development trials using a line and grab system of recovery in the modified tail section of XRL were completed in April. As a result of these trials, which included four drops positively buoyant and four drops in the negatively buoyant state, minor modifications will be carried out.

S E C R E T

(b) Water jettison system

Manufacturing work is now completed and trials will now commence to test this system of recovery in XR4.

(c) Instrumentation

The tape recorder mount and battery pack are nearing completion, and the instrument pack is progressing well. The design section are engaged upon the overall layout of the completed XR4 with a view to obtaining warshot weight at the correct C of G position. Detail designs are progressing on the transducer mounts and the switching system.

6.3 Shock measurements using other electronic instruments

(a) Peak "g" recorder Mk I No 1

This shock level indicator, modified to give time durations at two pre-selected "g" levels, was used successfully on ten drops before the store in which it was installed (19) was lost on a jettison release drop on 18th November 1964. As the results from this instrument were providing valuable information for use in setting up the shock recording store XR4, workshops were requested to produce an identical unit as soon as possible and install it in 08.

(b) Peak "g" recorder Mk I No 2

The new instrument was manufactured, calibrated and installed, and the first drop in the present series took place on 17th February, 1965. In assessing the results of the time-slice tests completed so far, three generalizations may be made:

- (i) Plotting the time-slice duration against % "g" the maximum duration envelope indicates that at 75% of the peak "g" measured the pulse may endure for 3 m.sec; at 50% of the maximum "g" it may last for 9 m.sec; whilst at 30% a pulse length of 18 m.sec has been recorded.
- (ii) At the lower "g" levels the minimum duration envelope indicated that 10g persists for not less than 3 m.sec, 8 g for 5 m.sec., and 7g for at least 10 m.sec.
- (iii) There is a clear demarcation between drops made at water entry angles less than 63° and greater than 70°. The shock pulses tend to fall into two groups of roughly similar form but of different "g" magnitudes: the greater shock occurring at the higher angles of water entry.

(c) Mechanical shock indicators

For water entry shock investigation the use of Reed Gauges, Inertia Switches and Impactographs has been discontinued, as these have all proved to have inadequate response characteristics, but the Impactograph will still be used to measure parachute opening shocks.

6.4 Low temperature tests on torpedoes and flight-in-air material

(a) Vessex Mk 5 Winterisation trial

An R.T.D.U. representative was sent to participate in the Winterisation Trials held at Fort Churchill in February/March 1965. An interim report will be issued shortly detailing the trials carried out and the recommendations made, but a summary of the main findings are listed overleaf.

S E C R E T

- (i) No difficulty was experienced in loading Mk 43 and Mk 44 torpedoes onto a Wessex Mk 5 at an outside air temperature of -33°C and windchill 2280.
- (ii) On the one mechanical jettison and one release drop carried out all the flight-in-air material functioned correctly.
- (iii) The scoopbulkhead plunger, which allows water to enter the torpedo and energise the battery, failed to open on most of the cold static tests carried out.
- (iv) The N.2 Mk I fuse was severely affected by both the cold and ice build up: the pull off loads of the plugs hydrostatic and locking increased by 200 to 300%; of which as a consequence the key ring type lanyard attachment distorted on the live drop, allowing the plugs to stay in the fuse, and the torpedo to fall un-armed.

(b) Type "C" breakaway band

As a result of the static cold tests carried out at Fort Churchill it was clear that neither low temperatures nor a reasonable amount of icing up would cause the band to malfunction. The bungees remained flexible at low temperature, and one pair were used on three successive temperature cycling tests without showing signs of deterioration. In view of these results the type C breakaway band is considered suitable for use under sub-arctic conditions, and no further low temperature tests on this component are necessary. (See paragraph 2.4).

(c) Type "R" release mechanism

Due to the very dry conditions which existed at Fort Churchill the protective cover for the type B release was not able to be tested under the conditions for which it was designed; but on one comparative test carried out using two mechanisms (one with and one without covers) only the covered one would have released at water entry. Very cold, dry weather had no serious effects on the mechanisms paddle release loads or in the relative movements of mating parts. It is felt, therefore, that no problem exists due to contraction, but that the exposed mechanism renders it liable to malfunctioning due to the ingress of snow, ice particles, or freezing rain.

This susceptibility to icing up exists, and under conditions of air temperatures below 0°C and freezing rain it could become a major hazard. For this reason it is recommended that climatic tests be initiated to investigate this problem more fully

S E C R E T

PART VII - SUMMARY OF DROPS FOR PERIOD 1st NOVEMBER 1964
TO 30th APRIL 1965

7.1 Torpedoes

<u>TRIAL ORDER</u>	<u>OBJECT OF TRIAL</u>	<u>NO. OF STORES</u> <u>DROPPED</u>
T/62/A	Development trials of parachutes and attachments for the release of Mk 44 torpedoes from fixed wing aircraft.	3
T/63C	Wasp HAS Mk 1 Limited CA clearance.	6
T/64/A	Carriage, release and jettison trials of UK Mk 44 and FC Mk 43-3 torpedoes from Gannet AEF Mk 3 aircraft.	24
T/64/D	Release flights to clear Shackleton Mk 3, Phosco 3 aircraft in Mk 30 and Mk 44 torpedo role.	231 } TORPS 21 DSB 155 MM 18 ASh 16 DC 21
T/64/F	Trials of US Mk 14 Mod 3 parachute release mechanism.	2
T/64/G	Air launch trials to investigate performance of Mk 43-3 torpedo fitted with primary battery.	8
T/65/A	Wessex HAS Mk 1 and 3 - carriage and release of DME buoys.	8
T/65/B	Wasp HAS Mk 1 - final clearance for carriage, release and jettison of 2 x UK Mk 44 Mod 0 torpedoes.	14
T/65/C	Wessex HAS Mk 1 - final clearance for the carriage, release and jettison of 2 x UK Mk 44 Mod 0 torpedoes.	5
E/64/C	Initial investigations into parachute opening and water entry shocks.	16
		<u>317</u>

7.2 OTHER TRIALS

P/65/A	Development and clearance trials - anti-submarine training indicator and smoke and flame floats.	74
B/65/A	Wessex helicopter aircraft Mk 1, 2 and 5 clearance for carriage, release and jettison of the Mk 11 depth charge	9
		<u>GRAND TOTAL 400</u>
T/64/A	To investigate range procedure in connection with 30° dives from Gannet aircraft. (1 section 30 minutes flying)	6 runs

S E C R E T

PART VII (Continuation of Summary of Drops)

<u>OTHER TRIALS</u>	<u>OBJECT OF TRIAL</u>	<u>NO. OF STORES DROPPED</u>
E/64/D	Measurement of vibration in a Mk 44 torpedo when carried on a Cornet AEW 3. (2 sorties 2 hours flying)	0
E/64/D	Measurement of vibration in a Mk 44 torpedo when carried by a Wasp helicopter. (6 sorties 2 1/2 hours flying)	0
T/63/E	Range photography test covering Canberra aircraft. (1 sortie 50 minutes flying)	0

S E C R E T

DISTRIBUTION

COPY NO.

Ministry of Aviation

D.A. Arm.	1
A.Arm. Plans	2
A.Arm. 1 (b)	3
A.Arm. 2(a)	4
A.Arm. 2(b)	5
A.Arm. 3	6
A/S Air PM	7
D(RM)/H	8
D.G.O.	9
T.I.L. (including 2 copies for Defence Research Staff)	10-15
Head of Weapons Division, R.A.F.	16
Weapons Divisions, R.A.F. (Project Division)	17-18
Library Weapons, Department, R.A.F.	19
Mechanical Engineering Dept. R.A.F. (Parachute Research)	20
Supt. of Armament, A.C.S.I.L., Boscombe Down	21
Secretary, Ordnance Board	22

Ministry of Defence (Naval)

D.C. (R. & D.)	23
D.U.S.N.	24
D.A.	25
D.C.A.	26
D.P.R.	27
D.M.R.	28
D.F.D.S. (A.C.S.I.L. Reports Section)	29
D.O.R.	30
D.T.P.	31
D.N.I.	32
D.C. (U), Bath (Including 1 copy for D.O.(T) British Naval Staff)	33-38
D.A.D. Bath	39-41
D.C. Shiver (D.W.E.) Bath	42
" " (D.T.E.) Bath	43-44
" " (D.W.C.) Bath	45-46
D.I.I. Bath	47
C.S.A.U. E. Portland	48-49
P.O. Submarines	50
P.O. Air (Home)	51
Captain, R.N.S. Vernon	52
Captain, R.N.S. Ariel	53
Officer in charge, T.T.U. Culrose	54
U.S. Naval Attache	55
R.A.N.I.O.	56-58
R.N.S.I.O.	59-60

Ministry of Defence (Air)

D. Weps, Eng.	61
D.O.R.	62
D.D. of O's (H)	63
A.S.I.D.N., Ballykelly	64

Ministry of Defence

D.S.I.	65
--------	----

Canadian Joint Staff

Naval members (including 1 copy for D.S.P. (Navy))	66-71
Air Member	72

R.C.A.F. Staff

73-74

U.S. Joint Services Leading Panel

75-86



*Information Centre
Knowledge Services
[dstl] Publications
Catalogue
Cells
AD 1600
2000-6218
[AD 1600-6218]
[AD 1600-6218]*

Defense Technical Information Center (DTIC)
8725 John J. Kingman Road, Suit 0944
Fort Belvoir, VA 22060-6218
U.S.A.

AD#: AD361292

Date of Search: 10 February 2009

Record Summary: AVIA 16/200
Aircraft Torpedo Development Unit progress reports Apr 1965
Former reference (Department): PR 1/65
Held by The National Archives, Kew

This document is now available at the National Archives, Kew, Surrey, United Kingdom.

DTIC has checked the National Archives Catalogue website (<http://www.nationalarchives.gov.uk>) and found the document is available and releasable to the public.

Access to UK public records is governed by statute, namely the Public Records Act, 1958, and the Public Records Act, 1967.
The document has been released under the 30 year rule.
(The vast majority of records selected for permanent preservation are made available to the public when they are 30 years old. This is commonly referred to as the 30 year rule and was established by the Public Records Act of 1967).

This document may be treated as UNLIMITED.